JACOBY·TARBOX®
A PRODUCT OF CLARK-RELIANCE

High Pressure Threaded Sight Flow Indicators

ASME Class 300, 600, 900, 1500

Section: T100
Bulletin: T100.15
Date: 07/2015
Supersedes: 08/2003

Jacoby-Tarbox® is *The World Leader* in high pressure threaded bulls-eye sight flow indicators. Jacoby-Tarbox is the only manufacturer to offer the highest pressure production unit as a standard. Engineered per the design criteria of ASME B31.1 & B31.3, Power and Process Piping Codes, incorporating the listed ASTM materials for all metals in the unit construction.

"Out-of-the-box Compliance"

ASME B31.1 & B31.3
CRN – All Provinces
API 614
NACE MR0175 / ISO15156-1 MRO103*
PED (Specify when ordering for proper tagging)

*All Wetted Metals

Process View Maximized
View matches or exceeds pipe inside diameter, allowing 100% unobstructed process observation of liquids, slurries, gases and solids.

Minimal Pressure Drop
Non-rotor models have unrestricted flow as all internal openings are no smaller than the pipe's inside diameter.

Safely View process properties such as color, clarity, air entrainment, and interface.

Economically View drain, lube, hydraulic, condensate, food and return lines.

Window and Shield Options:

- FM Approved dual window tempered borosilicate (2 per side / 4 total)
- UniShield® Window Protection - bonded PFA shielding for chemical resistance
- UniGlas® fused safety windows*

***Over *35 years without a single failure – ask us for details*.**

Standard Features:

- Single Window (1 per side / 2 total)
- Cast Body
- 100% Hydrotest (See schedule T100.35)

	Plain	Flapper	Rotor	Drip	Flutter
Class 300	S-100HPA-CL3(NF)	S-100HPA-CL3	S-300HPA-CL3	S-200HPA-CL3	S-100HPA-CL3-FLTR
Class 600	S-100HPA-CL6(NF)	S-100HPA-CL6	S-300HPA-CL6	S-200HPA-CL6	S-100HPA-CL6-FLTR
Class 900	S-100HPA-CL9(NF)	S-100HPA-CL9	S-300HPA-CL9	S-200HPA-CL9	S-100HPA-CL9-FLTR
Class 1500	S-100HPA-CL15(NF)	S-100HPA-CL15	S-300HPA-CL15	S-200HPA-CL15	S-100HPA-CL15-FLTR
Indicator	None	316 Weighted Flapper with 316 Pin	PTFE Rotor with 316 Pin	316 Drip Tube	Light Weight PTFE Flutter
Flow	Bi-Directional	Uni-Directional	Bi-Directional	Uni-Directional	Uni-Directional
Orientation	Horizontal or Vertical	Horizontal or Vertical Upward	Any	Vertical Downward or Horizontal	Any
Application	Observe presence or absence of fluid	Judge flow changes by flapper position	Indicates relative process velocity by rotation speed	Condensing gasses (drip) or partially full liquid lines	Gas flows. Low velocity liquid flow in full lines

16633 Foltz Parkway ● Strongsville, OH 44149 USA
Telephone: +1 440- 572-1500 ● Fax: +1 440- 238-8828

LOCAL REPRESENTATIVE
Yates & Co., Inc.
1 Hollywood Ave – Unit 22 HoHoKus, NJ 07423
201-345-3101 / info@yatesco.net
New Jersey, New York, & Connecticut

JACOBY·TARBOX®
A PRODUCT OF CLARK-RELIANCE

Part Number Matrix
High Pressure Threaded Sight Flow Indicators

CLASS 300 MODELS	Drawing
Up 750 psig (51.7 Bar)	T400.117

Model	Code
S-100HPA-CL3(NF)	TAZ
S-100HPA-CL3	TAZ
S-200HPA-CL3	TEZ
S-300HPA-CL3	TMZ
S-100HPA-CL3-DW(NF)	TAZX
S-100HPA-CL3-DW	TAZX
S-200HPA-CL3-DW	TEZX
S-300HPA-CL3-DW	TMZX

CLASS 600 MODELS	Drawing
Up 1500 psig (103 Bar)	T400.118

Model	Code
S-100HPA-CL6(NF)	TBZ
S-100HPA-CL6	TBZ
S-200HPA-CL6	TFZ
S-300HPA-CL6	TNZ
S-100HPA-CL6-DW(NF)	TBZX
S-100HPA-CL6-DW	TBZX
S-200HPA-CL6-DW	TFZX
S-300HPA-CL6-DW	TNZX

CLASS 900 MODELS	Drawing
Up 2250 psig (155 Bar)	T400.119

Model	Code
S-100HPA-CL9(NF)	TCZ
S-100HPA-CL9	TCZ
S-200HPA-CL9	TGZ
S-300HPA-CL9	TOZ
S-100HPA-CL9-DW(NF)	TCZX
S-100HPA-CL9-DW	TCZX
S-200HPA-CL9-DW	TGZX
S-300HPA-CL9-DW	TOZX

CLASS 1500 MODELS	Drawing
Up 3750 psig (258 Bar)	T400.120

Model	Code
S-100HPA-CL15(NF)	TDZ
S-100HPA-CL15	TDZ
S-200HPA-CL15	THZ
S-300HPA-CL15	TPZ
S-100HPA-CL15-DW(NF)	TDZX
S-100HPA-CL15-DW	TDZX
S-200HPA-CL15-DW	THZX
S-300HPA-CL15-DW	TPZX

CODES

Model	Size	Wetted Metal	Body	Indicator	Window	Gasket	Non-Wetted	Faceplate

Size	Code
1/4"	4
3/8"	6
1/2"	8
3/4"	10
1"	12
1-1/2"	16
2"	18

Faceplate	Code
Jacoby-Tarbox	1

Window Note:
"Window Material", "Trim Material", and for Quartz, "Gasket Material", must be picked together.

" T " = Tempered
" Q " = Quartz
" U " = UniGlas®

Trim Material	Code	
Carbon Steel (T-Boro Window)	1	T
316 SS (T-Boro Window)	2	T
Carbon Steel (Quartz Window)	4	Q
316 SS (Quartz Window)	5	Q
Carbon Steel (UniGlas Window)	6	U
316 SS (UniGlas Window)	7	U

Note: All steel trim limited to 600F (277C)

Body Material	(Max Temp)	Code
Carbon Steel (WCB)	(1000F/537C)	C
316 SS (CF8M)	(1500F/815C)	S
Bronze (B61)	(450F/232C)	B
316L SS (CF3M)	(1500F/815C)	6L
Hastelloy® C (CW12MW)	(1300F/704C)	HC
Alloy 20 (CN7M)	(600F/577C)	A
Monel® (M-35-1)	(900F/482C)	M
Duplex (Consult Factory For Code)		CFFC
Special Requirements		CFFC

Gasket choices for:
ALL Class 300 (CL3) & Class 600 (CL6)

Gasket Material	(Max Temp)	Code	
Neoprene	(250F/121C)	1	
Gylon® 3545	(500F/260C)	2	
Fiber (IFG® 5500)	(550F/287C)	3	
Graphite	(>800F/426C)	4	Q
Viton	(350F/177C)	5	

Body Material	Code
Standard NPT	1
Optional Butt Weld End	2
Optional Socket Weld End	3

Gasket choices for:
ALL Class 900 (CL9) & Class 1500 (CL15)

Gasket Material	(Max Temp)	Code	
~~Neoprene - Not Available~~		~~1~~	
Gylon 3545	(500F/260C)	2	
Fiber (IFG 5500)	(550F/287C)	3	
Graphite	(>800F/426C)	4	Q
~~Viton - Not Available~~		~~5~~	

Indicator Choices for 100's & 200's	Code
No Flapper = Plain (100 only)	0
316SS Flapper (100) / 316 Drip (200)	1
PTFE Flutter (100)	2

Indicator Choices for 300's	Code
Standard PTFE Rotor	1
316SS Rotor - Note: ONLY use when PTFE is not compatible with process or temperature exceeds 500F (260C)	2

Window Material	(Max Temp)	Code	
Tempered Boro Glass	(500F/260C)	1	T
T-Boro with UniShield®	(500F/260C)	2	T
Quartz Glass	(2012F/1100C)	4	Q
UniGlas w/ Steel Ring	(600F/315C)	5	U
UniGlas w/ Hast C Ring	(600F/315C)	6	U
UniGlas w/ Duplex SS Ring	(532F/277C)	9	U

Rating Notes:
Design Temperature: Unit Temperature rating based on the lowest "Max Temperature" of selected components (ie. body, glass, gaskets)
Design Pressure: Actual Unit Pressure rating based on body material as defined by ASME B16.5 material group.

16633 Foltz Parkway ● Strongsville, OH 44149 USA
Telephone: +1 440- 572-1500 ● Fax: +1 440- 238-8828

LOCAL REPRESENTATIVE
Yates & Co., Inc.
1 Hollywood Ave – Unit 22 HoHoKus, NJ 07423
201-345-3101 / info@yatesco.net
New Jersey, New York, & Connecticut