



**RCM Industries**  
110 Mason Circle, Suite D, Concord, CA 94520

For Sales Contact:

**Yates & Co., Inc.**

1 Hollywood Ave - Unit 22  
HoHoKus, NJ 07423  
201-345-3101 - info@yatesco.net

## Ammonia Low Flow Meter - Liquid Flowmeter



Ammonia service flow meters (liquid flowmeters) include a brass free construction throughout, stainless steel gear movement, gasketed case, and calibration for specific gravity, pressure and temperature. Available for stainless steel models only. The low flow meter is available with 1/2" female NPT connections for measuring the flow of liquid as low as 1 GPH.

### [How To Order](#)

#### **Standard Specifications:**

Accuracy:  $\pm 3\%$  F.S.  
Repeatability:  $\pm 1\%$  F.S.  
Pressure Max.: 180 psig (12.6 kg/cm<sup>2</sup>)  
Pressure Min.: 10 psig (0.67 kg/cm<sup>2</sup>)  
Temp. Max.: 212°F (100°C)  
Temp. Min.: -30°F (-34°C)

#### **Optional Specifications:**

Pressure Max.: 400 psig (28.1 kg/cm<sup>2</sup>)  
Pressure Min.: 10 psig (0.67 kg/cm<sup>2</sup>)  
Temp. Max.: 350°F (177°C)  
Temp. Min.: -80°C (-62°C)

Results 1 - 2 of 2

<a href="#">Item #</a>	<a href="#">Size</a>	<a href="#">Connection Type</a>	<a href="#">Series</a>	<a href="#">Process Connection</a>	<a href="#">Material</a>
<a href="#">1/2-73</a>	1/2 in	Threaded	7000	NPT	SST
<a href="#">15-73</a>	15 mm	Threaded	7000	BSP	SST

Results 1 - 2 of 2