



RCM Industries
110 Mason Circle, Suite D, Concord, CA 94520

For Sales Contact:

Yates & Co., Inc.

1 Hollywood Ave - Unit 22
HoHoKus, NJ 07423
201-345-3101 - info@yatesco.net

Ammonia Service Low Flow Meter - Gas Flowmeter



Ammonia service low flow meters (gas flowmeters) include a brass free construction throughout stainless steel gear movement, gasketed case, calibration for specific gravity, pressure and temperature. Available for stainless steel models only. The low flow meter is available with 1/2" female NPT connections for measuring the flow of gases as low as 10 SCFH.

[How To Order](#)

Standard Specifications:

Accuracy: $\pm 3\%$ F.S.
Repeatability: $\pm 1\%$ F.S.
Pressure Max.: 180 psig (12.6 kg/cm²)
Pressure Min.: 10 psig (0.67 kg/cm²)
Temp. Max.: 212°F (100°C)
Temp. Min.: -30°F (-34°C)

Optional Specifications:

Pressure Max.: 400 psig (28.1 kg/cm²)
Pressure Min.: 10 psig (0.67 kg/cm²)
Temp. Max.: 350°F (177°C)
Temp. Min.: -80°C (-62°C)

Results 1 - 2 of 2

Item #	Size	Connection Type	Series	Process Connection	Material
1/2-73	1/2 in	Threaded	7000	NPT	SST
15-73	15 mm	Threaded	7000	BSP	SST

Results 1 - 2 of 2